

CBD20-150
Electric Pedestrian
Pallet Truck

Advantages

Configuration and Performance

- Electronic power steering system,light and low noise.
- AC Driving system,No carbon brush,maintenance free.
- Electromagnetic,regenerative braking system.
- Automatic lifting limit,safety,energy saving.

Safety

- Curve automatic deceleration devices,more safe.
- Stepless speed control system,safe and quiet.
- Controller with Multiple automatic protection.
- Emergency reversing device/Emergency brake switch.



Options

- 170Ah VRLA Battery-Built-in charger.
- Handle upright walking function.

HELI CBD20-150

Feature		
Model		CBD20-150
Loading capacity	kg	2000
Load center	mm	600
Wheel base	mm	1390
Operating type		Walkie
Wheels		
Wheels type		PU
Wheel quantity Driving wheel/Balance wheel/Bearing wheel		1/1/4
Driving wheel size	mm	Φ248×75
Bearing wheel size	mm	Φ84×80(Double wheels)
Balance wheel size	mm	Φ115×55
Dimension		
Min.fork lowered height	mm	85
Max.fork lifting height	mm	195
Max.lifting height	mm	110
Overall fork width	mm	540/600/650/685
Inside width between forks	mm	200/260/310/345
Fork length	mm	1150/1200
Fork width	mm	170
Fork thickness	mm	75
Overall length	mm	1750
Overall width	mm	720
Overall height(With handle)	mm	1385
Overall height(Without handle)	mm	850
Min.Turning radius	mm	1575
Min.Aisle width for pallets 800×1200	mm	1900
Min.Aisle width for pallets 1000×1200	mm	1940
Performance		
Travel speed,laden/unladen	km/h	3.5/4.0
Lift speed,laden/unladen	mm/s	20/25
Lowering speed,laden/unladen	mm/s	40/30
Gradeability,laden/unladen	%	6/16
Electrical configuration		
Drive motor	kW	AC 1.5
Lift motor	kW	DC 1.2
Steering motor	kW	DC 0.15
Battery voltage / capacity	V/Ah	24/210
Brake		Electromagnetic/Regenerative
Controller		ZAPI (Options CURTIS)
Weight		
Battery weight	kg	192
Service weight with battery	kg	605

* Details of specifications and equipment are based on information available at time of printing and may change without notice.



ANHUI HELI CO., LTD.
ADD: NO.668 Fangxing Street,Economical Development Zone,Hefei,P.R.China
TEL : (86 551)63639068 (America) 63639258 (Europe) 63639358 (Asia)
63662105 (Africa & Middle East) 63639530 (Key Accounts division)
63662105 (Wheel loader)
FAX : (86 551)63639966
WEBSITE : <http://www.heliforklift.net>
Email : heli@helichina.net

AUTHORIZED DEALER

EPS | AC
Steering automatic deceleration
Typical model,Most popular in Europe & America